
M404 - Waveform Generator




Features

- 4 independent high speed waveform generators
- 4 independent low speed waveform generators
- Maximum output frequency: 1.75 MHz for high speed channels, 435 kHz for low speed channels
- Frequency resolution: 0.00035 Hz
- 2 arbitrary waveforms for each channel, each defined by 64 k 12 bit-words, adjustable gain
- Fast switching between the waveforms
- Weighted intermixing of both tables of a channel
- Adjustable gain
- Output voltage range: -10V .. +10V
- Output voltage res.: 12bit, corresponding to 4,8mV
- · Perfectly designed for usage with passive wheelspeed sensor simulation for trucks
 - Simulation of loosing and missing teeth
 - Wheel angle resolution: 0.0055deg
 - Wheel rotation speed resolution: 0.021rpm
 - Maximum wheel rotation speed: 50,000rpm
- Galvanic isolation
- In the field hardware upgrade by updating the FPGA

Use Cases

- Emulating passive wheel speed sensor signals in truck ABS/ESC test applications
- Testing fail-safe mechanismns by simulation of missing teeth
- Generating arbitrary waveforms

Block Diagram



Technical Data	
Output channels	4 independent high speed waveform generators
	4 independent low speed waveform generators
Output voltage range	-10V +10V
Output voltage resolution	12bit (corresponds to 4,8mV)
Output current per channel	20mA with internal supply
	85mA with external supply (optional)
Maximum output frequency	1.75MHz for high speed channels
	435kHz for low speed channels (depending on user waveform)
Frequency resolution	0.00035Hz (depending on user waveform)
Waveform table size	64k 12bit words (each table)
Number of waveform tables	2 for each channel
Sample rate	3.5MHz for high speed channels
	875kHz for low speed channels
Address space	• A08D16
	• A24D32
Available connectors	25 Pin SubD connector, female

Order Information

rder Number	IO-M404
-------------	---------

Alternatives

	M400	For generation of active wheel speed sensor signals
- 1		· · · g - · · · · · · · · · · · · · · ·